



- | | | | | | Total Weight | |
|----|-------------------------------------|--------|--|--------------------------------------|--------------|--|
| 21 | Motor Base Support Plate | S-2602 | | 5.5 (10.0) x 10.0 (10.0) x 2.0 (16) | 0.16 | |
| 22 | Motor base plate | S-2602 | | 5.5 (10.0) x 10.0 (10.0) x 1.5 (12) | 0.12 | |
| 23 | Internal Coupling | S-2602 | | 7.0 (16.0) x 5.0 (10.0) | 0.12 | |
| 24 | Motor Base Mount | S-2602 | | 7.0 (16.0) x 5.0 (10.0) | 0.12 | |
| 25 | Internal Coupling, 1/4 HP, 1500 RPM | S-2602 | | 1.0 (16.0) x 5.0 (10.0) | 0.23 | |
| 26 | Motor base size 1/4 HP, 1500 RPM | S-2602 | | 1.0 (16.0) x 5.0 (10.0) | 0.23 | |
| 27 | Grab screw | S-2602 | | 1/2 (12.0) x 1/4 (6.0) | 0.03 | |
| 28 | Grab screw | S-2602 | | 1/2 (12.0) x 1/4 (6.0) | 0.03 | |
| 29 | Grab screw | S-2602 | | 1/2 (12.0) x 1/4 (6.0) | 0.03 | |
| 30 | Grab screw | S-2602 | | 1/2 (12.0) x 1/4 (6.0) | 0.03 | |
| 31 | Grab screw | S-2602 | | 1/2 (12.0) x 1/4 (6.0) | 0.03 | |
| 32 | Grab screw | S-2602 | | 1/2 (12.0) x 1/4 (6.0) | 0.03 | |
| 33 | Support Plate | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.14 | |
| 34 | Motor support Hub | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.14 | |
| 35 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 36 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 37 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 38 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 39 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 40 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 41 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 42 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 43 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 44 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 45 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 46 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 47 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 48 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 49 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 50 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 51 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 52 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 53 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 54 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 55 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 56 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 57 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 58 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 59 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 60 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 61 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 62 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 63 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 64 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 65 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 66 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 67 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 68 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 69 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |
| 70 | Internal Coupling | S-2602 | | 1.0 (16.0) x 1.0 (16.0) x 1/2 (12.0) | 2.23 | |

Alt. No.	Suffix	Description	Chgd.	Chkd.	Appd.	Date
Matl. CARBON STEEL			Qty. 1		Part No.	
Designation : AGITATOR Clients: NELCON ENGINEERS			Name		Date	
			DRN BY	SP	07-01-25	
			CHKD BY	RS	07-01-25	
			APPO BY	DP	07-01-25	
			Scale : 1:5.0			
File Size : A1			 Drg. No. agit03e			